



# SALA Professional Single point, multi-purpose fall arrest harness

## Description

This CE marked harness which conforms to EN361, is equipped with a rear fall arrest attachment point for fall protection purposes.

It has adjustments on the chest, shoulders and legs to provide a perfect fit to give maximum comfort and safety during work.

The 'SUREFIT' limited stretch elastic system, allows the user to move with the maximum amount of freedom, but in a fall, the limited stretch does not allow the harness to come out of position on the body.

## Main features

- Simple and quick to fit and adjust
- Adjustable rear fall arrest attachment point
- Adjustment on chest, shoulders, legs
- Sub pelvic strap
- 'SUREFIT' limited stretch elastic system
- All webbing ends sewn.
- Available in Standard and Large versions

## Applications

Adapted for most fall arrest situations.

- Pitched roof
- Flat roof
- Scaffolding/steel work
- Structural steel
- Edge protection



## Associated Products

With this harnesses fall arrest point the following product are recommended

- Sala retractable fall arrest blocks conforming to EN360
- Sala fall arrest energy absorbing lanyards conforming to EN355

**KB1100S**

(N-100S)



## SALA Professional Single point, multi-purpose fall arrest harness

### Technical specification

- Webbing - 45mm width, 100% Polyester, Breaking strength >3400 daN
- Thread - High strength, 100% Polyester
- D-ring - Breaking strength >3000 daN, Heat treated alloy steel, White zinc plating finish.
- Buckles (leg, shoulders) - Breaking strength >1500 daN, Heat treated alloy steel, White zinc plating finish.
- Individual serially numbered
- Net Weight - 1025g
- Conforms to standard – EN361
- System attachment point breaking Strength >15KN

### Options

#### KB1100S/L

Large size version of harness.

#### KB1200S

The same harness base with the addition of a work positioning belt.

#### KB1300S

The same harness base with the addition of front arrest point.

