



## SALA Professional Single point, multi-purpose fall arrest harness with work positioning belt

### Description

This CE marked harness which conforms to EN361 & EN358, is equipped with a rear fall arrest attachment point for fall protection purposes.

The harness also includes a work positioning belt, fully adjustable to ideally suit most positioning work.

It has multiple adjustments to provide a perfect fit to give more comfort and safety during work.

The 'SUREFIT' limited stretch elastic system, allows the user to move with the maximum amount of freedom, but in a fall, the limited stretch does not allow the harness to come out of position on the body.

### Main features

- Simple and quick to fit and adjust
- Adjustable rear fall arrest attachment point
- Adjustable side work positioning belt attachment points
- Adjustment on chest, shoulders, waist, legs
- Sub pelvic strap
- 'SUREFIT' limited stretch elastic system
- All webbing ends sewn.

### Applications

Adapted for most fall arrest situations where the addition of a work positioning belt would be useful.

- Pole work
- Pitched roof
- Flat roof
- Scaffolding/steel work
- Structural steel
- Work Positioning
- Edge protection



### Associated Products

With this harnesses fall arrest point the following product are recommended

- Sala retractable fall arrest blocks conforming to EN360
- Sala fall arrest energy absorbing lanyards conforming to EN355

With the side work positioning attachment points the following products are recommended

- Sala work positioning lanyards conforming to EN358

**KB1200S**

(N-200S)



## SALA Professional Single point, multi-purpose fall arrest harness with work positioning belt

### Technical specification

- Webbing - 45mm width, 100% Polyester, Breaking strength >3400 daN
- Thread - High strength, 100% Polyester
- D-rings - Breaking strength >3000 daN, Heat treated alloy steel, White zinc plating finish.
- Buckles (leg, shoulders) - Breaking strength >1500 daN, Heat treated alloy steel, White zinc plating finish.
- Buckle (waist) - Chrome plated steel
- Harness individual serially numbered
- Net Weight - 1920g
- Conforms to standard – EN361 & EN358
- System attachment points breaking Strength >15KN

### Options

#### KB1100S

The same harness with no work positioning belt.

#### KB1300S

The same harness with no work positioning belt, and with the addition of front arrest point.

#### KB1400S

The same harness/belt base with a larger/padded work positioning belt comfort pad, and with the addition of front arrest point.

