



SALA Professional 2 point, multi-purpose fall arrest harness, with rescue attachment points

Description

This CE marked harness is equipped with a front and rear fall arrest attachment points for fall protection purposes, and conforms to EN361.

It has in addition rescue attachments points conforming to EN1497, built into the shoulders. These attachment points are stowed away on the shoulders during normal working, and are instantly available for rescue purposes.

It has multiple adjustments to provide a perfect fit to give more comfort and safety during work.

The 'SUREFIT' limited stretch elastic system, allows the user to move with the maximum amount of freedom, but in a fall, the limited stretch does not allow the harness to come out of position on the body.

Main features

- Front and rear fall arrest attachment points
- Adjustable rear fall arrest attachment point
- Stowed away rescue attachments points
- Adjustment on shoulders and legs
- Sub pelvic strap
- 'SUREFIT' limited stretch elastic system
- All webbing ends sewn.

Applications

Adapted for most fall arrest situations. and particularly suited for confined space work, where the additional security of having an integrated rescue harness is demanded.

- Confined Spaces
- Pitched roof
- Flat roof
- Scaffolding/steel work
- Structural steel
- Ladder climbing
- Edge protection



Associated Products

With the front or rear fall arrest points the following product are recommended

- Sala retractable fall arrest blocks conforming to EN360
- Sala fall arrest energy absorbing lanyards conforming to EN355

The front fall arrest point is ideally situated to be used with

- Sala vertical fall arrest systems conforming to EN353-1 & EN353-2

For confined space work using the rescue attachment points

- Sala Tripods **KM1PT7** & **KM1PT9** and Man riding winches **KT2PW60L** & **KT2PW120L**



Capital Safety Group www.capitalsafety.com

France Tel +33 (0)4 97 10 00 10 Email information@capitalsafety.com

UK Tel +44 (0)1928 571 324 Email info@csgne.co.uk



KB1300SR

(N-300SR)



SALA Professional 2 point, multi-purpose fall arrest harness, with rescue attachment points



Technical specification

- Webbing - 45mm width, 100% Polyester, Breaking strength >3400 daN
- Thread - High strength, 100% Polyester
- D-rings - Breaking strength >3000 daN, Heat treated alloy steel, White zinc plating finish.
- Buckles (leg, chest, shoulders) - Breaking strength >1500 daN, Heat treated alloy steel, White zinc plating finish.
- Individual serially numbered
- Net Weight – 1395g
- Conforms to standard – EN361
- System fall arrest attachment points breaking Strength >15KN
- System rescue attachment points breaking Strength >15KN (**Rescue points MUST be used together**)

Options

KB1300S

The same harness base without the addition of Rescue straps.

