



## SALA Professional multi-purpose, 2 point fall arrest harness with work positioning belt

### Description

This CE marked harness which conforms to EN361 & EN358, is equipped with a front and rear fall arrest attachment point for fall protection purposes.

The harness also includes a generously padded work positioning belt, fully adjustable to ideally suit most positioning work.

It has multiple adjustments to provide a perfect fit to give more comfort and safety during work.

The 'SUREFIT' limited stretch elastic system, allows the user to move with the maximum amount of freedom, but in a fall, the limited stretch does not allow the harness to come out of position on the body.

### Main features

- Front and rear fall arrest attachment points
- Adjustable rear fall arrest attachment point
- Adjustable side work positioning belt attachment points
- Large work positioning belt comfort pad
- Adjustment on shoulders, waist, legs
- Sub pelvic strap
- 'SUREFIT' limited stretch elastic system
- All webbing ends sewn.

### Applications

Adapted for most fall arrest situations where the additional comfort of a work positioning belt would be useful.

- Pole work
- Mast tower work
- Pitched roof / Flat roof
- Scaffolding/steel work
- Structural steel
- Ladder climbing
- Work Positioning
- Edge protection



### Associated Products

With the front or rear fall arrest points the following product are recommended

- Sala retractable fall arrest blocks conforming to EN360
- Sala fall arrest energy absorbing lanyards conforming to EN355

The front fall arrest point is ideally situated to be used with

- Sala vertical fall arrest systems conforming to EN353-1 & EN353-2

With the side work positioning attachment points the following products are recommended

- Sala work positioning lanyards conforming to EN358



Capital Safety Group [www.capitalsafety.com](http://www.capitalsafety.com)

France Tel +33 (0)4 97 10 00 10 Email [information@capitalsafety.com](mailto:information@capitalsafety.com)

UK Tel +44 (0)1928 571 324 Email [info@csgne.co.uk](mailto:info@csgne.co.uk)



**KB1400S**

(N-400S)



## SALA Professional multi-purpose, 2 point fall arrest harness with work positioning belt

### Technical specification

- Webbing - 45mm width, 100% Polyester, Breaking strength >3400 daN
- Thread - High strength, 100% Polyester
- D-rings - Breaking strength >3000 daN, Heat treated alloy steel, White zinc plating finish.
- Buckles (leg, shoulders, chest) - Breaking strength >1500 daN, Heat treated alloy steel, White zinc plating finish.
- Buckle (waist) - Chrome plated steel
- Harness individual serially numbered
- Net Weight - 2215g
- Conforms to standard – EN361 & EN358
- System attachment points breaking Strength >15KN

### Options

#### KB1300S

The same harness with no work positioning belt.

#### KB1900

Specialised harness, Front and rear fall arrest points, and work positioning belt, designed for persons who will use work positioning for extended periods.

#### KB1EXO/MB

Unique 'EXOFIT' harness, Front and rear fall arrest points, and work positioning, For users who demand unrivalled comfort and security.

