



SALA Specialist, 2 point fall arrest harness with work positioning belt

Description

This CE marked harness which conforms to EN361 & EN358, is equipped with a front and rear fall arrest attachment point for fall protection purposes.

The harness also includes a generously padded work positioning belt, the side work positioning attachment points are fixed, and perfectly angled, to allow the user to make the connection instinctively.

It has multiple adjustments to provide a perfect fit to give more comfort and safety during work.

The 'SUREFIT' limited stretch elastic system, on the shoulders and legs, allows the user to move with the maximum amount of freedom, but in a fall, the limited stretch does not allow the harness to come out of position on the body.

Main features

- Front and rear fall arrest attachment points
- Fixed side work positioning belt attachment points
- Large work positioning belt comfort pad
- 4 tool attachment swivel clips on belt
- Adjustment on shoulders, waist, legs
- Padded sub pelvic strap
- 'SUREFIT' limited stretch elastic system on legs, and shoulders
- All webbing ends sewn.

Applications

Adapted for most fall arrest situations where the additional comfort of a work positioning belt would be useful.

- Pole work
- Mast tower work
- Pitched roof / Flat roof
- Steel work
- Structural steel
- Ladder climbing
- Work Positioning



Associated Products

With the front or rear fall arrest points the following product are recommended

- Sala retractable fall arrest blocks conforming to EN360
- Sala fall arrest energy absorbing lanyards conforming to EN355

The front fall arrest point is ideally situated to be used with

- Sala vertical fall arrest systems conforming to EN353-1 & EN353-2

With the side work positioning attachment points the following products are recommended

- Sala work positioning lanyards conforming to EN358



Capital Safety Group www.capitalsafety.com

France Tel +33 (0)4 97 10 00 10 Email information@capitalsafety.com

UK Tel +44 (0)1928 571 324 Email info@csgne.co.uk



KB1900S

(N-900S)



SALA Specialist, 2 point fall arrest harness with work positioning belt

Technical specification

- Webbing - 45mm width, 100% Polyester, Breaking strength >3400 daN
- Elastic webbing – 45mm width, Nylon & Polyester, Breaking strength >2700 daN
- Thread - High strength, 100% Polyester
- Fall arrest attachment points - Breaking strength >2200 daN, Heat treated alloy steel, White zinc plating finish
- Work positioning attachment points - Breaking strength >2200 daN, stainless steel, polished plating finish.
- Buckles (leg, shoulders, chest) - Breaking strength >1500 daN, Heat treated alloy steel, White zinc plating finish.
- Buckle (waist) - Chrome plated steel
- Harness individual serially numbered
- Net Weight - 2720g
- Conforms to standard – EN361 & EN358
- System attachment points breaking Strength >15KN

Options

KB1EXO/MB

Unique 'EXOFIT' harness, Front and rear fall arrest points, and work positioning. For users who demand unrivalled comfort and security.

KB1400S

A simpler harness, less padding, with Front and rear fall arrest points, and work positioning.



CE

Capital Safety Group reserves the right to modify the specification of this product without prior notice. Descriptions, colours, pictures and diagrams herein appear for guidance only.